DTSC 8022A (9/93) EPA 8700-22 TSDF SENDS THIS COPY TO GENERATOR WITHIN 30 DAYS. (Generators who submit hazardous waste for transport out-of-state, produce completed copy of this copy and send to DTSC within 30 days.)

DO NOT WRITE BELOW THIS LINE.

950597

CALL

8

6



SAFETY-KLEEN CORP. (DESIGNATED FACILITY)

DOUGLAS AIRCRAFT

Safety-Kleen Corp. manages the above waste through its recycling and fuels programs in accordance with all applicable elements of the land disposal restrictions.

Generator Company:___

CATOGO 613976 (DESIGNATED FACILITY) EPA ID NO.

		e de Touris Maria de la composición de la c						
	SOUTH YA		CA 92704					
Inder manifest / sales service e restricted under 40 CFR Pa a copy of this form must be ke	rt 268. In accord	ance with 40 CFR Part 268.7, the generator hereby provisor and facility for five (5) years from the date of waste shi	noted below is shipping to you a waste determined to des notice that the waste is restricted from land disposal ipment.					
WASTE NAME	WASTE		TREATMENT STANDARD (mg/l) OR METHOD					
Waste Petroleum Naphtha 105	D001, D006, D008, D018, D035, D039, D040,	Ignitable Liquid (High TOC Subcategory) Halogenated Organic Compounds (HOC's) ≥ 1000 mg/l Cadmium Lead Benzene Methyl Ethyl Ketone Tetrachloroethylene Trichloroethylene	Incineration (INCIN), fuel substitution (FSUBS)					
H Waste Petroleum Naphtha 140	D001, D006, D008, D018, D039,	Ignitable Liquid (High TOC Subcategory) Cadmium Lead Benzene Tetrachloroethylene	INCIN, FSUBS, or RORGS (40 CFR 268.42)(non-waste water) 1.0 (non-waste water) 5.0 (non-waste Water Not Established Not Established					
Cyclonic, 150 Premium Solvent OR Actrel Solvent Statement specific	D006, D008, D018, D039, D040,	Cadmium Lead Benzene Tetrachloroethylene Trichloroethylene	1.0 (non-waste water) 5.0 (non-waste Water Not Established Not Established Not Established					
TCLP is not available)			** · · · · · · · · · · · · · · · · · ·					
T E Waste Petroleum Naphtha (sludges fro Safety-Kleen Service Center Operations	D001, D006, D008, D018, D039,	Ignitable Liquid (High TOC Subcategory) Cadmium Lead Benzene Tetrachloroethylene	INCIN, FSUBS, or RORGS (40 CFR 268.42)(non-waste water) 1.0 (non-waste water) 5.0 (non-waste Water) Not Established Not Established					
X E S Waste Compound Cleaning Liquid/ Immersion cleaner 6	D006, D008, D018, D021, D027, D035, D039, D040,	HOC's ≥ 1000 mg/l Cadmium Lead Benzene Chlorobenzene 1, 4-Dichlorobenzene Methyl Ethyl Ketone Tetrachloroethylene Trichloroethylene	INCIN (40 CFR 268.42)(non-waste water) 1.0 (non-waste water) 5.0 (non-waste Water Not Established					
O NUMBER	SPECIFIC GRAVITY		BE THAN 30% UNUSUAL UNUSUAL MATERIALS INCLUDED/ADDED? (Y/N)					
440-00192 440-03203 NA 440-03988 560-49520 110-57508								
SPECIFIC GRAVITY ACCEPTANCE GUIDELI	NES -088-05-1	/187 14 663263 9438						
		of the waste (via Material Safety Data Sheets for the chemical(s) used, and the process which created the waste).					

printed on recycled pep

CAD0865100:15

EPA ID NO .: _

TRANSPORTER

2200+ CA

SCHEDULED SERVICE TERRITORY

SCHEDULED SERVICE WEEK

663263

REFERENCE NUMBER

38

114-435-0605 BILL THIEBERT

LDR REQ'D

9503 5 NORMANDIE

DOUGLAS AIRCRAFT

7-088-05-7187-9

ATTN JUE E DEPT 71606-14

90502

714-435-10-714-435-9206 B I T L O

	E9\/I(HANDLING	ANDLING CREDIT CODE CODE				CALE	2 TAV	CODE		F	.	РОППОМ	
			6843						CODE		SALEŞ TAX CODE 05-095-8937						BALANCE		OVER 60 DAYS
BUS	INESS	CHAIN		CUSTOMER P.O.	NI IMBED		GENERATO	P'SICHS		HONE #	0.5-09					VICE TAX	C.O.M.S.	TAV	PRODUCT TA
	VPE			JUSTOWER F.U.	NOWBER							92	—				U.U.M.S.	IAX	
- 1	9	0079					310-	333	,-0,	900	NO	92.	3 1	0.1	• 0	825		-	•0825
SE	RVIC							SERVICE TERM							ARKS	0362			
\vdash		440	-00192	220.79	18.21	23	8.96			08					<u> </u>				
_		440	-03203	220.75	18.21	23	8.96		<u> </u>	08	<u> </u>	-			<u> </u>	<u>.</u>	-,		
\vdash		440	-03988	220.79	18.21		8.96			0.8/	ļ								
L		<u>560</u>	<u>-49520</u>	216.00	.00	21	6.00			08		20	1			/GRE	YMILL:	<u>\$</u>	
_		110	<u>-57508</u>	142.25	11.74	15	3.99			12	\			·				Carrier .	·
L					·		3						····		_				<u> </u>
_		·				<u> </u>					1				\vdash				
<u> </u>		<u> </u>				 				٠	1	 			-	1.33		200 7 0000	
┝						 			\vdash		-				-				
H	_ -		- 			 					 	 			-		V Sees €		
-				 	 				 	+	 	 			-				<u> </u>
 		# ^=	AI					•	<u> </u>		G000	POOR		TONIO TO TO		YES NO			YES N
ļ	e E	TOT	AL SECTION	1.				MACHI & CLEA	NE CONDI ANLINESS	TION	Z			CALS IN PLA AND LEGIBLE ISIBLE LINK	Æ	Z	MACHINE PRO LOCAL PHON		Acres de la
_				1020.50								_		ASTALLED MERGENCY C	OPNO		AFFIXED T	O MACHIN	⋷
				LEÁSE CHECK APPRO USEPA				CON	ASSEMBLY VOITION RATOR			065	0	LID UNOBST	ructed_	ERATOR	SPENT SOLVE ACCEPTANCE	CRITERIA	<u> </u>
W				USEPA RANSPORTER ID NO.				USEP#	A ID NO.			865			STA	TE ID NO.	CONTAIN	ER	T:
	-			NCLUDING PROPER				(.טו טו	NO.	TAINERS	- QL	JANTITY	w	, UNIT T/VOL	SK DC	OT NUMBER	SIZE		I CERTIFY TH
				STIBLE LI					 ,		١.						51630	כקנ	MY TOTAL WAS
-				1THA) NAI 3,0035,00				•	0	DM	10	0	G	١		585		7	WITHIN ONE O
_				CLEANI			KG#2	<i>,</i> ,	μ_				_					+	CATEGORIES. 0 TO
				NE) 8 NAI			E D C #4	anı	1	DM		6				566	11	1	220 LBS./MONTH
-				3,0021,00						OH		0	G	1		300	111	1	
Ë		0,00	OGIDOLO	,, 5021,00	27,000	J, D.O.	3900	+0 ;	-	-				+				+	INITIALS 220 LBS, TO
				. å					ĺ.								- 1 1		2,200 LBS./MONTH
							14		1 /										
\vdash									-	\vdash	-		\dashv	-+			-	+	INITIALS GREATER THAN
						18.3													2,200 LBS./MONTH
						1			1		•		ì				1 1	Ì	XD9
ה	FSIC	NATE	FACILITY	NAME AND A	DDRESS	S	AFETY	/K	1 FE	N C	DRP		- 1	ISAE	:DA	ID NO.	CATO	106	13976
			SOUTH Y		55,1200		TA A					9270							13976
					•		RODUC							JIAII	ַ טו	NO.	011704	,,,	,0,,0
	Pi	RODUCT NUI	MBER		DESCRIPTION		.CDOC	1 J/	MSDS		PRICE	Uh		QUANTIT		SALES	TAX	Ŧ	LINE TOTAL
									GIVEN		1802	- 3/1		DELIVERE	D	AMOUNT -	- 100	+	
										+								-	
0900						_				+			\dashv		+			+-	
															+			+	
												+	\dashv		+			+	
							MENT TO:	1							+				
P	묩	ş	CASH	TOTAL RECE	IVED I AI	PPLY PAY!	VICINI I U.			FAI DI	RODL	JCTS A	AMC	UNT			1		
PAYM	CHCL	-	CASH HECK NUMBER	TOTAL RECE		PPLY PAYI		\dashv	10	IAL FI									
P.A≻≥m2	с-попъ	о 		TOTAL RECE		DDAY'S SERV		ows C					HIS T	<u>RANSA</u>	<u> </u>	OTAL SER	VICE AMOU	UNT	1001 0
₽A≻≦шZ	Œ⊞O⊞~>ju≪	02	HECK NUMBER	TOTAL RECE	TC	DDAY'S SERV	/ICE/SALE	ows C					HIS T	RANSAC D IN TH ECLAM) E 1		VICE AMOU I ABOVE)	UNT	1086.8-
PAYMEN		CT ON INV	HECK NUMBER	TOTAL RECE		DDAY'S SERV	/ICE/SALE	ows C					HIS T CATE THE R L TER ORMA E ARE	RANSAC D IN TH ECLAM, IMS AN TION AI MADE	TEADO A	(FROM	ABOVE)	UNT	1086.8-
₽Α≻⊠ш≾		02	HECK NUMBER	TOTAL RECE	TC	DDAY'S SERV	/ICE/SALE	ows C		MY AC ILESS O IT RECE GREEME IONS, AI 3 ON TH REOF.	COUNT THERW IVED SE NT, AD ND, OTH E REVE	FOR TISE INDICTIONAL INFORMATION OF THE INFORMATION	HIS T ICATE THE R L TER ORMA DE ARE	RANSAC DIN THECLAM MS AN TION AI MADE	TEA-DD A	(FROM	L DUE		
PAYMEN		ON INV	HECK NUMBER		TC	CDAY'S SERVICUS BALA T \$ AMEX VISA	/ICE/SALE			MY AC NESS O NT RECE GREEME IONS, A GON TH EREOF.	CCOUNT THERW IVED SE NT, AD ND OTH E REVE	FOR TISE INDICATIONAL INDICATIONAL INFORMATION INFORMATION INFORMATION INFORMATION INTO THE PROPERTY INTO TH	named m	ateriais are p	корелу с	(FROM	ABOVE) L DUE packaged, marked a	ınd labele	d, and
	CRE	ON INV	HECK NUMBER . # NO. CREDIT CARD N		TC	DDAY'S SERV	VICE/SALE		HARGE ION UN AYMEN ION AI SONDI PEARING ART HE	MY AC NLESS O IT RECE GREEME IONS, AI 3 ON TH REOF, "This is are in	CCOUNT THERW IVED SE NT, AD OTH E REVE s to certify th proper condi	FOR TISE INDICATIONAL INDICATIONAL INFORMATION INFORMATION INFORMATION INFORMATION INTO THE PROPERTY INTO TH	named m a nottatnoc	aterials are p according to	корелу с	TOTAl	ABOVE) L DUE packaged, marked a	ınd labele	d, and

DIRECTIONS FOR SAFE, EFFECTIVE USE OF THE SAFETY-KLEEN PARTS WASHER UNIT... AND SAFETY-KLEEN IMMERSION CLEANER UNIT. READ BEFORE USING.

I. SAFETY-KLEEN PARTS WASHER SOLVENT

Safety-Kleen solvent is a high flash hydrocarbon solvent sultable for use in degreasing applications.

A Combustibility
Safety-Kisen solvent is a combustible material. Safety-Kieen selvent is a combustible material. That means it will burn under certain conditions. Your Safety-Kieen parts washer should not be installed where it can be exposed to heat, sparks or open flame; nor should there be any smoking nearby while a Safety-Kieen parts washer is in use.

Use dry chemicals, form or carbon dicade to extinguish flame. The safety fusible link is designed to melt and allow the cover to fall shut and smother any flames.

- Safety-Kleen solvent is by definition considered only slightly toxic to relatively non-toxic. Avoid inhaling or swallowing the Safety-Kleen solvent and its coming is contact with your skin, face and eyes. If taken internally, splashed in your eyes, inhaled, or upon contact with your skin, face or eyes, follow the instructions

1. Skin contact-Remove contaminated clothing Wash skin twice with soap and water. If imitation or pain develops or persists, consult a physician immediately.
2. Eyes-Wash with planty of water. Call a physician immediately.
3. Internally-Do not induce vomiting. Call physician immediately. Guard against inhaling solvent into lungs.
4. Inhalation-Avoid Breathing solvent vapors. Adequate ventilation should be provided in any area where the Safety-Kieen parts washer is being used.
5. Clothes-If your clothes become saturated with solvent, change clothes immediately. Above all, do not smoke or go near an open flame or sparks while clothes are wet with solvent.

II. -USE OF YOUR SAFETY-KLEEN PARTS WASHER

A: Avoid leaving large parts or tools in your parts washer which might prevent the lid from closing in case of a fire in your place of business.

B. Avoid leaving convent soaked rags either in your parts washer, wadded up on workbenches or in uncovered containers. Do not put a solvent soaked rag in your pootest, it will cause a skin rash at point of contact.

you use a scaking pan, make certain that its height is less than the sink height and empty it into the sink as soon as you have finished using your parts washer.

D. Do not let open pans of solvent sit either in the sink or anywhere else around your place of business.

Safety-idean cannot accept for reclamation materials other than the solvents originally supplied and the materials removed from the parts cleaned. Therefore, additional solvents or other materials must not be added to the machine. You should note that even small amounts of low flash point materials (such as

gasoline) lower the flash point of Safety-Rieen solvent substantially.

If, for any reason, the fusicle link should break or fall, call you local Safety-Rieen branch for a replacement. Do not use a cotter key or other device to hold the lid up. The fusible link is chacked each time a Safety-Rieen man services your unit and if the safety link is faulty, it will be replaced. If it breaks between

our service periods, call for a replacement trimediately.

G. Do not place extremely heavy objects in one end of the parts washer unit. The parts washer is very stable but an extremely heavy object could result in the washer being appeal if it is bumped, causing the solvent to dump out on your floor.

Washer being 1951 in its burninger, causing the solvent to dump out on your noor.

If, Any and all solvent spills should immediately be soaked up with absorbent material, such as Safety-Kleen absorbent, and the solvent soaked material should be removed from the shop area. Contact Safety-Kleen for disposal.

If, Part of Safety-Kleen's service is immediate repair or replacement of your parts washer should there be any failure of any kind. Simply call your local Safety-Kleen branch. The number is on the parts washer lid.

J. Your Safety-Kleen parts washer should be plugged into a grounded outlet. Under no discumptances should a grounding prong be enlipted off the plug.

Safety-Kleen provides, at no charge, an adapter which permits grounding on two-prong electrical outlets. Ro Do not remove solvent from your parts washer.

III. BAFETYALEEN IMMERSION CLEANER SOLVENT

Immersion Oldaner Solvent is a imputure of aromatic naphthia cleaning solvents and N-Methyl-2-Pyrrolldone for use in removing varnish formed on automotive parts such as carbifretors, transmissions, etc.

ts euch es carbéretors, transmissions, etc.

Combustible material: That means it will burn under certain conditions. Your Safety-Kieen Immersion Cleaner should not be installed where it can be exposed to heat, sparks or open flamer, nor should there be any emoking nearby while a Safety-Kieen Immersion Cleaner unit i

be instance where it can be exposed to read, epons of the linicase of fire
Use dischemicals, foam or carbon dioxide to extinguish flame.
Use dischemicals, foam or carbon dioxide to extinguish flame.
Toxicity
This solvent contains aromatic 150, N-Methyl-2-Pyrrolidone and Monoethanolamine. DO NOT BEEATHE VAPORSI HARMFUL OR FATAL TE SWALLOWEDI
DO NOT INDUCT VOMITING! CALL A PHYSICIAN IMMEDIATELY. KEEP AWAY FROM EYES! WASH IMMEDIATELY AND COPIOUSLY WITH RUNNING
WATER, CALL A PHYSICIAN.
Avoids contact with bidn and clothing. If solvent is inadvertently spilled on skin or cicties wash immediately with running water. Remove clothes as quickly as nossible and clother.

IV. SAFE USE OF YOUR SAFETY-KLEEN IMMERSION CLEANER

1.3 Keep away from host, sparks and flame. Do not place not parts in solvent.
2. Use only solvent provided. DO NOT ADD OTHER CHEMICALS TO THE CLEANING SOLVENT, INCLUDING BUT NOT LIMITED TO KEROSENE, FUEL OIL, GASOLINE, DETERGENTS, CHLORINATED SOLVENTS OR ANY MATERIAL CONTAINING POLYCHLORINATED SIPHENYLS.

p ATTINATIVE use of any other solvents potentially causes a hazardous condition over which Safety-Kleen has no control.

1994. Use city in well ventilated locations. Avoid repeated and/or prolonged breathing of vapors: Vapors are heavier than air and will collect in low areas.

5. Avoid contact with eyes. Use protective eye wear such as chemical goggles.

Should you desire any further information about our solvent, our service or our company, please do not have to write or call. Phona No. 1-800-669-5740. The Safety-Kleen parts washer is covered under Directive #100-22, issued by the Occupational Safety and Health Administration's Director, Office of Standards. dated February 20, 1973.

RECLAMATION AGREEMENT

Safety-Kleen agrees as part of this machine placement, to collection from Customer the used solvent supplied by Safety-Kleen to the machine. Collection of the used solvent supplied by Safety-Kleen to the machine. Collection of the used solvent supplied by Safety-Kleen to the machine. Safety-Kleen shall reclaim the used solvent for radelivery. Safety-Kleen has the capacity and is permitted to accept, store and reclaim the spent solvents described on this document.

Safety-Kleen and Customer agree that this agreement is intended to satisfy the requirements of 40 Code of Federal Regulations 262.20(e), as amended, and any state regulations which implement said provision. Customer agrees to keep this form on file for 3 years from the date of last service.

ADDITIONAL TERMS AND CONDITIONS

Safety-Kleen agrees to furnish the above service on its equipment, and Customer agrees that all servicing, repair and maintenance of the equipment shall be performed by Safety-Kleen only. All equipment and solvent shall remain the property of Safety-Kleen and shall be returned to Safety-Kleen upon termination of service. Customer agrees to pay for replacement of equipment due to loss or damage.

Customer agrees that it will not mix the solvent provided hereunder with other materials, that it will not introduce any substance into the solvent which is egulated as hazardous wasto or which contains polychlorinated biphenyls, and that it will not otherwise cause the alteration of the characteristics or components of the solvents.

Customer agrees to indemnify and hold harmless Safety-Kleen, its officers, directors, employees and agents from and ageinst any and all losses, expenses, damages, demands and claims based upon any injury, death or damage ansing out of Customer's acts or omissions and to pay any and all damages costs and expenses (including reasonable attomerys fees) in connection therewith. Customer agrees that Safety-Kleen is not responsible for any violation, loss or claim arising from noncompilance with pollution control laws caused by release of solvent to the environment from the unit or resulting from customer handling, but not illimited to, spills into adjacent waterways, sever lines or ground water, however caused. Safety-Kleen accepts responsibility for any spill caused by its agents in connection with the installation or servicing of the machine by Safety-Kleen.

Customer agrees that service hereunder will continue until Customer or Safety-Klean terminate service. The Termination will only be effective after receipt by the non-terminating party of written notice of termination to be received on the greater of 30 days prior to the date of cancellation or the length of the service interval appearing in the Machine Placement section; provided, however, if Customer is a party to a One-Year Service Agreement with Safety-Kleen, Customer shall not have the light to terminate seid Contract except as provided in said Contract.

The total due on the reverse side is subject to an interest charge of the lessor of 11/2% per month (18% per month) or the maximum rate allowed by law on any unpaid invoices that are

In the event of detault, Safety-Kleen shall be entitled to recover costs of collection, including reasonable attorney's fees.

In the event for credit card issue, refuses to accept the credit card charge for this transaction set forth on the front of this document, you are authorized to charge the amount of this properties. transaction to my Safety-Kleen accounts